## Ads-Mod, Fehler beim Aufruf

| Autor | Nachricht | |
|---|---|---|
| Holger | Betreff des Beitrags: Ads-Mod, Fehler beim Aufruf | Mi 06.Jun, 2012 16:12 |

Hallo,

wenn ich bei mir die Ads-Seite aufrufe bekomme ich fast immer:

> Zitat:
>
> Failed sending email :: PHP ::
>
> DEBUG MODE
>
> Line : 246
> File : emailer.php

Rufe ich danach die Seite auf, ist alles wieder normal.

Ich denke, dass entstand nach dem Upgrade vom PHP auf den neuesten Stand.
Wonach müsste ich mal schauen?

Zeile 246 ist die letzte message_die am Ende:

Code:

```
 // Send the mail out to the recipients set previously in var $this->address
// +MOD : MegaMail
 function send($email_format = 'text')
// -MOD : MegaMail
 {
  global $board_config, $lang, $phpEx, $phpbb_root_path, $db;

    // Escape all quotes, else the eval will fail.
  $this->msg = str_replace ("'", "\'", $this->msg);
  $this->msg = preg_replace('#\{([a-z0-9\-_]*?)\}#is', "' . $\\1 . '", $this->msg);

  // Set vars
  reset ($this->vars);
  while (list($key, $val) = each($this->vars))
  {
   $$key = $val;
  }

  eval("\$this->msg = '$this->msg';");

  // Clear vars
  reset ($this->vars);
  while (list($key, $val) = each($this->vars))
  {
   unset($$key);
  }

  // We now try and pull a subject from the email body ... if it exists,
  // do this here because the subject may contain a variable
```

```
  $drop_header = '';
  $match = array();
  if (preg_match('#^(Subject:(.*?))$#m', $this->msg, $match))
  {
   $this->subject = (trim($match[2]) != '') ? trim($match[2]) : (($this->subject != '') ? $this->subject : 'No Subject');
   $drop_header .= '[\r\n]*?' . preg_quote($match[1], '#');
  }
  else
  {
   $this->subject = (($this->subject != '') ? $this->subject : 'No Subject');
  }

  if (preg_match('#^(Charset:(.*?))$#m', $this->msg, $match))
  {
   $this->encoding = (trim($match[2]) != '') ? trim($match[2]) : trim($lang['ENCODING']);
   $drop_header .= '[\r\n]*?' . preg_quote($match[1], '#');
  }
  else
  {
   $this->encoding = trim($lang['ENCODING']);
  }

  if ($drop_header != '')
  {
   $this->msg = trim(preg_replace('#' . $drop_header . '#s', '', $this->msg));
  }

  $to = $this->addresses['to'];

  $cc = (count($this->addresses['cc'])) ? implode(', ', $this->addresses['cc']) : '';
  $bcc = (count($this->addresses['bcc'])) ? implode(', ', $this->addresses['bcc']) : '';

// +MOD : MegaMail
  if ($email_format == 'html')
  {
   // Build html header
   $this->extra_headers = (($this->reply_to != '') ? "Reply-to: $this->reply_to\n" : '') . (($this->from != '') ? "From: $this->from\n" : "From: " .
$board_config['board_email'] . "\n") . "Return-Path: " . $board_config['board_email'] . "\nMessage-ID: <" . md5(uniqid(time())) . "@" .
$board_config['server_name'] . ">\nMIME-Version: 1.0\nContent-type: text/html; charset=" . $this->encoding . "\nContent-transfer-encoding:
8bit\nDate: " . date('r', time()) . "\nX-Priority: 3\nX-MSMail-Priority: Normal\nX-Mailer: PHP\nX-MimeOLE: Produced By phpBB2\n" .
$this->extra_headers . (($cc != '') ? "Cc: $cc\n" : '')  . (($bcc != '') ? "Bcc: $bcc\n" : '');
  }
  else
  {
   // Build text header
   $this->extra_headers = (($this->reply_to != '') ? "Reply-to: $this->reply_to\n" : '') . (($this->from != '') ? "From: $this->from\n" : "From: " .
$board_config['board_email'] . "\n") . "Return-Path: " . $board_config['board_email'] . "\nMessage-ID: <" . md5(uniqid(time())) . "@" .
$board_config['server_name'] . ">\nMIME-Version: 1.0\nContent-type: text/plain; charset=" . $this->encoding . "\nContent-transfer-encoding:
8bit\nDate: " . date('r', time()) . "\nX-Priority: 3\nX-MSMail-Priority: Normal\nX-Mailer: PHP\nX-MimeOLE: Produced By phpBB2\n" .
$this->extra_headers . (($cc != '') ? "Cc: $cc\n" : '')  . (($bcc != '') ? "Bcc: $bcc\n" : '');
  }
// -MOD : MegaMail
```

```
// Send message ... removed $this->encode() from subject for time being
if ( $this->use_smtp )
{
 if ( !defined('SMTP_INCLUDED') )
 {
  include($phpbb_root_path . 'includes/smtp.' . $phpEx);
 }

 $result = smtpmail($to, $this->subject, $this->msg, $this->extra_headers);
}
else
{
 $empty_to_header = ($to == '') ? TRUE : FALSE;
 $to = ($to == '') ? (($board_config['sendmail_fix']) ? ' ' : 'Undisclosed-recipients:;') : $to;

 $result = @mail($to, $this->subject, preg_replace("#(?<!\r)\n#s", "\n", $this->msg), $this->extra_headers);

 if (!$result && !$board_config['sendmail_fix'] && $empty_to_header)
 {
  $to = ' ';

  $sql = "UPDATE " . CONFIG_TABLE . "
   SET config_value = '1'
   WHERE config_name = 'sendmail_fix'";
  if (!$db->sql_query($sql))
  {
   message_die(GENERAL_ERROR, 'Unable to update config table', '', __LINE__, __FILE__, $sql);
  }

  $board_config['sendmail_fix'] = 1;
  $result = @mail($to, $this->subject, preg_replace("#(?<!\r)\n#s", "\n", $this->msg), $this->extra_headers);
 }
}

// Did it work?
if (!$result)
{
 message_die(GENERAL_ERROR, 'Failed sending email :: ' . (($this->use_smtp) ? 'SMTP' : 'PHP') . ' :: ' . $result, '', __LINE__, __FILE__);
}

return true;
}
```

| Autor | Nachricht | |
|---|---|---|
| oxpus | Betreff des Beitrags: Re: Ads-Mod, Fehler beim Aufruf | Mi 06.Jun, 2012 20:32 |

Hallo,

da du über PHP direkt sendest, müsstest du prüfen, ob die Einstellungen dazu in der php.ini auch passen.
Besser wäre aber über einen SMTP-Server zu senden.
Der ist entweder auf deinem Server drauf oder du kannst auch einen externen nehmen.
Damit bist du auf jeden Fall flexibler, kannst schneller auf Fehler reagieren, da du die Einstellungen selber ändern kannst und SMTP-Server können nach und nach die E-Mails verarbeiten, blockieren also in der Regel nicht so lange wie die PHP-Mail-Funktion, die erst wieder das Script weiter arbeiten lässt, wenn die E-Mail durch ist (ob mit oder ohne Fehler ist dabei egal).

| Autor | Nachricht | |
|---|---|---|
| Holger | Betreff des Beitrags: Re: Ads-Mod, Fehler beim Aufruf | Do 07.Jun, 2012 08:54 |

Hm, alle anderen Mails gehen ja raus ... PM, New reply usw.

| Autor | Nachricht | |
|---|---|---|
| oxpus | Betreff des Beitrags: Re: Ads-Mod, Fehler beim Aufruf | Do 07.Jun, 2012 14:20 |

Ich habe ja nicht gesagt, dass PHP-Mail nicht funktioniert, aber wohl bei dir nicht immer fehlerfrei.
Oder die eingestellte E-Mail-Adresse ist fehlerhaft?
Zumal auch keine konkrete Fehlermeldung angezeigt wird, ist PHP-Mail ggf. hier nicht verfügbar gewesen...